UMA Attorney's Docket No.: 28955.1055

Applicant: Hitoshi KUMA
In Re: Not yet assigned

Filed : Herewith Page : 3 of 5

Amendment to the Claims

1. (Original) An organic electroluminescent device comprising:

a transparent electrode,

a counter electrode arranged opposite to the transparent electrode,

one or more intermediate conductive layers and one or more organic emitting layers arranged between the transparent electrode and the counter electrode,

wherein the difference between n_a and n_b is 0.2 or less when n_a is the refractive index of an intermediate conductive layer and n_b is the refractive index of an organic emitting layer.

2. (Original) An organic electroluminescent device comprising:

a transparent electrode,

a counter electrode arranged opposite to the transparent electrode,

one or more intermediate conductive layers and a plurality of organic emitting layers sandwiching an intermediate conductive layer therebetween, the intermediate conductive layers and the organic emitting layers arranged between the transparent electrode and the counter electrode,

wherein the difference between n_a , and n_b and/or n_c is 0.2 or less when n_a is the refractive index of an intermediate conductive layer, n_b is the refractive index of a first organic emitting layer and n_c is the refractive index of a second organic emitting layer, the intermediate conductive layer sandwiched between the first and second organic emitting layers.

Applicant: Hitoshi KUMA Attorney's Docket No.: 28955.1055

In Re : Not yet assigned

Filed: Herewith Page: 4 of 5

3. (Currently Amended) The organic electroluminescent device according to claim 1 or 2, wherein the intermediate conductive layer, the refractive index of which is n_a, is a laminate comprising a layer having a higher refractive index than n_b and/or n_c and a layer

having a lower refractive index than n_b and/or n_c.

4. (Currently Amended) The organic electroluminescent device according to claim 1 or

2, wherein the intermediate conductive layer, the refractive index of which is na, is a layer

comprising a mixture of a material having a higher refractive index than n_b and/or n_c and a

material having a lower refractive index than n_b and/or n_c.

5. (Currently Amended) The organic electroluminescent device according to claim 1 or

2, wherein the intermediate conductive layer, the refractive index of which is na, comprises a

material having a low refractive index and a transparent conductive material selected from

oxides, nitrides, iodides and borides of metals.

6. (Original) The organic electroluminescent device according to claim 5, wherein

the material having a low refractive index is a metal halide, and the transparent conductive

material is a conductive metal oxide.

7. (Currently Amended) The organic electroluminescent device according to claim 1 or

2, wherein the absorption coefficient (unit: $1/\mu m$) of the intermediate conductive layer, the

refractive index of which is n_a, is 2.5 or less.

8. (Currently Amended) A display comprising the organic electroluminescent device of

claim 1 or 2.